2.8P





Zeal Motor Inc. 90 Blvd de l'Aeroport, Bromont Quebec, Canada J2L 1S9 579.319.0060 sales@zealmotor.com WWW. FATTRUCK.COM

2.8P



PERFORMANCE		ENGINE		TIRES		OPT
Payload Passengers capacity Maximum speed on land Maximum speed on water Maximum uphill & downhill	2200 lb (1000 kg) 8 (2 front + 6 rear) 25 mph (40 km/h) 3.1 mph (5 km/h) 35°/ 70%	Make Model Emission standards Number of cylinders Displacement	Caterpillar C2.2 Turbo diesel Tier 4 final (no DPF) 4 cylindres 135 po ³ (2.22 L)	Front & Rear Pressure Pressure control	FAT TRUCK [®] LGP 1640 x 640 x 610 0.5 to 4 lb/po ² (0.035 to 0.28 kg/cm ²) Preset automatic pressure control	Front w Additio Rear Hi Front a
				FUEL SYSTEM		Studs
Maximum sidehill Turning radius	22°/ 40% 0°	Horsepower @ 2800 RPM Torque @ 1400 RPM	153 p0 (2:22 L) 67 hp (50 kW) 153 lb-pi (208 N-m)	Capacity Average fuel autonomy	21 US Gal (80 L) 12 h	Engine Canopy, Heater
	4900 lb (2217 kg)	Cooling Syste	Liquid cooled	STANDARD EQUIPMENT		Front Custo
Ground pressure fully loaded	1.6 lb/po ² (0.11 kg/cm ²)	ELECTRICAL		Doors	Lockable 2 front seats with 3-points seat belts Front, brakes, position, flashers, dome Electric Front ladder with grab handles	Roof ra Exterio Back u Rear R Rear s Directi
SAFETY FEATURES ROPS EPA Brakes	ISO 3471 TIER 4 Final Automatic safety brake	Voltage Alternator capacity Battery capacity Battery type	960 CCA Horn AGM Ingress	Lights Horn Ingress		
DIMENSIONS		TRANSMISSION		Standard color Fire extinguisher	Red or white 2.5 lb ABC	Front, Extra
Height Length Width		Type Final drive	Hydrostatic Carbon fiber synchronous belts	Bilge pump Cup holders First aid kit	2.0 10 10 0	4 corn Electro Hydra Cold v
Ground clearance	20.7 in (526 mm)	BRAKES		Front and rear bumpers Lockable fuel cap		Ventila Storaç Rear I
CONTROLS		Brakes	Positive deceleration			
Controller Steering Display	Microprocesseur Joystick Color display	Park brakes	through hydrostatic transmission Brake disc applied pressure released	Operator & Maintenance manual		Tow p Wheel Transp Transp
WARRANTY			F			Amph
Limited 1 year / 1000 hours (Which ever comes first)						Air co Back Varia



vinch nal battery itch nd rear shackles for ice & hydraulic heater 110 V y, 2-person cab / defroster vindshield with wiper 1 color ick r mirrors p camera OPS eats with safety belts onal light with remote control side and rear light LED bar eater er LED beacon lights nic inclinometer ilic capstan kit eather package tion fan e box ldder ickage Pods™ ortation trailer ortation rack bious trailer ditioning ıp alarm ble cooling fan for engine 4-way camera system Hot sticks storage tubes

