2023 Mudd-0x 8x8 XL

Lingine		
Туре	Gasoline EFI	
Model	XL57	XL85
Brand	Kubota	Ford
Power Output	57 HP / 42 kW	85 HP /63 kW
Torque	86.7 lbs. / 117.5 Nm	137 lbs. / 185 Nm
Displacement	1537 cc	2,499
Electrical	105 Amp	94 Amp
Cooling	Liquid-Cooled	
Battery	65 S	eries

Transmission

Transmission	Mudd-0x Hydrostatic
Brakes	Hydrostatic and Hydraulic Braking

Controls & Instrumentation

OUTLI DIS CLITISCI OTTICITACION	
Steering	Ergonomic Left and Right Steering Controls
Parking Brake	Ratchet Style Mechanical
Instrumentation	Full Instrumentation Dash Panel
Gauges	Full Engine Power View & Diagnostics
	Fuel Gauge
	Volt Meter
	Hour Meter
	Coolant Temperature
	Hydraulic Temperature
Warning Lights	Check Engine
	Low Oil Pressure
	Neutral Light
	Parking/Emergency Brake

Chassis, Body & Lights

Ullassis, Dudy & Lights	•
Frame	Powder coated steel for long life and durability
Drive System	#60-2 (Twin 60) Roller Chain
Axles	1.500" Solid Steel
Body	Vacuum formed upper body, lower body and skid plate, made from High Molecular Weight Polyethylene (HMWPE)
Tires	26" x 14" x 12" Mudd-0x Vendetta on 12" Mudd-0x Bead Lock Rim
Lighting	LED Headlights & LED Tail Lights
	LED Brake & Reverse Lights w/ Optional Steering Wheel

Performance

1 CITOITHANCE	
Speed - Land	17-25 mph (27-40 km/h) [A]
Speed - Water	3 mph (5 km/h) [B]
Load Capacity - Land	2,000 lbs. (907 kg)(distributed evenly) Less the weight of
	any accessories [C]
Load Capacity - Water	1,000 lbs. (454 kg)(distributed evenly) Less the weight of
, ,	any accessories [C]
Turning Circle	Zero turning radius, machine counter-rotates
Towing Capacity	2,500 lbs. (1,134 kg) [G]
Seating Capacity - Land	4 to 6 [D]
Seating Capacity - Water	2 to 4 [D]
Rear Bench Seat	Optional

Mudd-0x, Inc. 8525 W 750 N Shipshewana, IN 46565 Phone: 260-768-7221 Fax: 260-768-3074 www.muddox.net info@muddox.net



Custom Colors Available Upon Request









Safety

Safety	Fold down Roll Over Protection System with seat belts for
	front two passangers. Rear Roll Over Protection System is
	available as an option. Mudd-0x Hydrostatic precision
	control drive system enables safe control at all times while
	maneuvering in the most difficult terrains.
Fuel Capacity	10.5 US Gallons
Operating Conditions	All weather, all terrain, -40°F to +110°F (-40°C to +43°C)

Ground Clearance

Ground Clearance	14" at center of vehicle 8" outer edge of vehicle
Ground Pressure	On Tires: 2 psi [D]
	Tracks: 0.5 psi [D]

Operation & Convenience

operation & convenience	
Self-Extraction Winch	5,000 lb. Capacity
Storage	Lockable glove box, Built in Cup Holders
	12.5" x 28" Insert area over Engine Cover
Electrical Output	12V Outlet, Dual Port USB Outlet
Rilge Pump	Standard

Waight C Dimonsions

weight & Dimensions	
Shipping Weight	2,290 lbs.
Dimensions	123" Long 68" Wide
	79" High with Roll Bar Up, 61" High with Roll Bar Down (on 26 x 14 x 12" Vendetta Tires)
Approach and Departure	25° Maximum

Warranty

A/C Unit

Warranty	1 year or 500 hours limited warranty on Mudd-Ox
	Engine: See manufacturer's manual [E]

Specifications are subject to change without notice.

[A] Top speed depends on terrain conditions and drive train options.

[B] Depends on water conditions, only operate in calm water without a current (No large lakes, open waters, oceans.)

[C] See Owner's manual for accessory listing and weight.

[D] Depending on weight of person, cargo and accessories onboard

[E] See Owner's Manual for full warranty information.

[F] Provides better flotation and allows for more carrying capacity in the water.

[G] Approximate Towing Capacity, depends on surface type and vehicle load as well as incline. Max Hitch Tongue Load is 200 lbs. (98 kg)

Accessories

Light Bar 12-48"

A/ C UTIIL	LIGHT Dal 12-40
A/C Unit Brush Guard	Outboard Motor
Automatic Chain & Bearing Lubrication	Rear Accessory Carrier - Main Mount
Auxiliary Switch Panel	Rear Seat - Standard
Auxiliary Hydraulics	Rear Seat - Bench
Axle Locking Hubs	Rescue
Bearing Grease Zerk Relocation	Safari Rack (Full/Half Lengths)
Brush Cage (Full/Half Length)	Snow Plow - 85"
Brush Guard	Snow Plow - Boss V Blade
Cab - Aluminum	Spare Carrier - 5 Gallon Fuel Can
Cab - Canvas (Full/Half Combo)	Spare Carrier - Tire
Cab - Canvas Rear Enclosure	Tire - Dual Wheel Kit
Cab - Stereo Kit	Tool Box
Controls - Remote Control	Tracks - 16" Wide Adair
Controls - Steering Wheel	Tracks - 20" Wide Ripsaw
Cargo Liner	Transport Tie Downs
Cargo Platform	Twin Roll Bar Package
Dump Bed	Winch - Synthetic Rope
Engine Remote Oil Drain	Winch - 5000 lbs. Rear Mount
Fender Kit	Windshield
Float - Catwalk	Windshield Cover - Cab
Float - Front	Windshield Washer
Heater w/ Defrost	Windshield Wiper

Version 1/11/2023