





# **Power & Traction** in Action

### **Kodiak K6 with 5 Cubic Yard Dump Box**

DIMENSIONS / WEIGHT				
Overall Length	241" with plow & dump box			
Overall Width	101"			
Overall Height	105" in transport position			
Base Carrier Weight	14,000 lbs			
Ground Clearance	20"			
Weight & Payload - Basic Vehicle - Payload Capacity - GVWR	14,000 lbs 12,000 lbs 28,000 lbs			
Deck Area	87" x 87" (approximately)			
PERFORMANCE DATA				
Maximum speed	8 mph			
Inside turning radius	0 ft.			
Climbing Ability - Uphill - Side-hill	35° (70%) 15° (27%)			
Ground Pressure	3.6 PSI nol load, 5.6 loaded			
Normal Driving Range	12 Hours (40 U.S. gallon fuel tank)			
ENGINE				
Make	Deutz AG			
Model	TCD 3.6 L4, 134 HP, 4 cylinder			
Displacement	3.6 liters			
DEF Tank	2.6 gals.			
Fuel capacity	50 gals.			
Torque	369 ft lbs. @ 1,600 RPM			
OPTIONAL ENGINE				
Make	JCB Power Systems			
Model	Ecomax 448 TA4, 173 HP, 4 cylinder			
Displacement	4.8 liters			

FRAME / SUSPENSION			
Туре	Corten Welded Tub		
Suspension	Walking beam with double twin rocker arm bogey wheels		
Wheels	16 steel wheels		
Size	12" steel with oil hub		
Suspension system com • 2 independent idler whe	es with: els with oil hubs & steel face seals		

## TRACKS

One piece 24" rubber tracks with steel reinforcements

Independent dual joysticks with cable control for each track

El	Æ.	СТ	R	<b>ICA</b>

Voltage	12 V
Battery Capacity	850 CCA
Alternator Capacity	120 Amps

# POWER TRAIN FOR HYDROSTATIC DRIVE

Transmission	Hydrostatic, 2-speed
Parking Brakes	Multi-disc, spring applied & pressure released
Service Brakes	Positive deceleration via hydrostatic transmission

### **CARRIER STANDARD FEATURES**

- 1-Man Open Cab
- · Vinyl seat with mechanical suspension
- 2 point seat belt
- Full instrumentation • Fire extinguisher
- Backup alarm

- 2 High powered LED Front lights,
- 1 Rear light and 1 Strobe
- Driver's side deck ladder
- Electronic engine protection system · Primary fuel filter with water separator
- Operations, Service and Parts Manual

#### **OPTIONAL EQUIPMENT & ACCESSORIES**

- 2 Way front plow
- 12,000 lb to 17,500 lb electric winches
- 18,000 lb hydraulic winch
- 1-Man Closed cab
- Air Conditioning Rear view camera

- Additional LED lights
- Spark arrestor
- Cold weather package
- Extreme Cold Weather Package
- 173 hp engine Front brush guard

- Side brush guard
- DOT Road Lighting
- Pintle hook
- 100 Hours service kit Additional parts & service manuals





Power & Traction in Action



Payload 12,000 lbs **Dump Box Capacity 5 Cubic Yards** 64464446



# KODIAK CRAWLER CARRIERS ARE AVAILABLE WITH PAYLOADS RANGING FROM 6 TO 15 TONS AND CAN BE CONFIGURED WITH A WIDE VARIETY OF OPTIONS TO MEET ALL OF YOUR NEEDS.



**Dump Box capacity 5 cubic yards** 



Max speed 8 MPH, Payload 12,000 lbs



Patented walking beam with double twin rocker arm bogie wheel suspension keeps the track in full contact with the ground and absorbs impacts



Low ground pressure gives excellent flotation on soft ground and 36" fording capability



Kodiak K6 is powered by a 134 HP engine

**KODIAK CRAWLER CARRIERS** CAN ALSO MOUNT CRANES, WATER OR FUEL TANKS, **SPRAY TANKS OR SPREADERS** 





Kodiak climbs a 35 degree slope with ease and with excellent sideslope stability



**Digger Derrick Mounting** 



**Flatbed Mounting**