







FULL GUIDE AND TECHNICAL SPECIFICATIONS

DIMENSIONS / WEIGHT		
Overall Length	229" (with plow)	
Overall Width	101"	
Overall Height	106" in transport position	
Base Carrier Weight	12,500 lbs	
Ground Clearance	20"	
Weight & Payload - Basic Vehicle - Payload Capacity - GVWR	12,500 lbs 12,000 lbs 28,000 lbs (two-man cab), 24,000 lbs (one-man cab)	
Deck Area	108" x 92"	
PERFORMANCE DATA		
Maximum speed	8 mph	
Inside turning radius	0 ft.	
Climbing Ability - Uphill - Side-hill	35° (70%) 15° (27%)	
Ground Pressure	2.23 PSI no load, 4.36 loaded	
Normal Driving Range	12 Hours (40 U.S. gallon fuel tank)	
ENGINE		
Make	Deutz AG	
Model	TCD 3.6 L4, 134 HP, 4 cylinder	
Displacement	3.6 liters	
DEF Tank	2.6 gals.	
Fuel capacity	50 gals.	
Torque	369 ft lbs. @ 1,600 RPM	

FRAME / SUSPENSION				
Туре	Corten Welded Tub			
Suspension	Walking beam with double twin rocker bogey wheels			
Wheels	16 steel wheels			
Size	12" steel with oil hub			
Suspension system comes with: • 2 independent idler wheels with oil hubs & steel face seals • 2 x rear drive sprockets				
TRACKS				
One piece 24" rubber tracks with steel reinforcements				
STEERING				
Independent dual joysticks with cable control for each track Steering Wheel (optional)				
ELECTRICAL				
Voltage	12 V			
Battery Capacity	1,060 CCA			
Alternator Capacity	120 Amps			
POWER TRAIN FOR HYDROSTATIC DRIVE				
Transmission Parking Brakes Service Brakes	Hydrostatic, 2-speed Multi-disc, spring applied & pressure released Positive deceleration via hydrostatic transmission			
CARRIER STANDARD FEATURES				
<ul> <li>2-man cab with climate control</li> <li>Vinyl seat with mechanical suspension</li> <li>Seat belt</li> <li>Full instrumentation</li> <li>Fire extinguisher</li> <li>Backup alarm</li> <li>Horn</li> </ul>	<ul> <li>2 High powered LED Front lights,</li> <li>1 Rear light and 1 Strobe</li> <li>Driver's side deck ladder</li> <li>Electronic engine protection system</li> <li>Primary fuel filter with water separator</li> <li>Operations, Service and Parts Manual</li> </ul>			

OPTIONAL EQUIPMENT & ACCESSORIES			
<ul> <li>2 Way front plow</li> <li>16,500 lb electric winch</li> <li>18,000 lb hydraulic winch</li> <li>Air Conditioning</li> <li>Rear view camera</li> </ul>	<ul> <li>Additional LED lights</li> <li>Spark arrestor</li> <li>Cold weather options</li> <li>Extreme Cold Weather options</li> <li>Front brush guard</li> </ul>	<ul> <li>DOT Road Lighting</li> <li>Pintle hook</li> <li>100 Hours service kit</li> <li>Additional parts &amp; service manuals</li> <li>3 point seat belt</li> </ul>	

### 



8650 Darnley Road Mont-Royal, Québec Canada H4T 1M4 1-800-985-8665

UTVINT.COM



# **Excellence by design**

Marking a significant advancement in all-terrain performance, the Kodiak K6 introduced a revolutionary suspension redesign featuring a patent-pending walking beam. Built with two sets of twin rocker arm bogey wheels, the redesign delivers unparalleled traction: maximizing track-to-ground contact for the most capable crawler carrier yet.



## **KODIAK K6 FIRETRACK**

#### RAISE THE BAR.

When it comes to wildfire mitigation and suppression, accessibility of fire sites is crucial. During a wildland fire, those sites are oftentimes off-road - making it difficult to access with traditional wheeled vehicles.

That's where we come in.

Designed for extreme mobility, the Kodiak K6 FireTrack offers unparalleled all-terrain handling, topped with an expertly designed fire package, the Kodiak FireTrack raises the bar: offering unmatched off-road suppression ability, advanced mitigation capability and overall response time improvement.

### Suppression starts here.

The Kodiak K6 FireTrack comes standard with a precision-built medium flow skid system that is designed to support your wheeled fleet. Featuring a lighter line and lower flow rate, the fire package is ideal for quick attack scenarios: offering both traditional and UHP (10 GPM) firefighting capability.

The skid system is completely customizable and can handle both foam and organic, USDA approved water enhancing gel concentrates.

#### **Selected Skid Features:**

- Centrifugal pump with 130gpm flow rate at 130psi
- 300 gallon custom poly tank with 10 gallon foam or gel concentrate line
- Two 1.5" ouputs & one 2.5" drafting inlet
- Optional TurboDrive UHP pump with 12gpm flow rate at 800psi to 8gpm flow rate at 1200psi



#### Selected Crawler Carrier Features:

 Two-man closed cab design with climate control 12,000 lb payload

- Advanced track & walking beam design
- 134 HP engine
- 2.23 psi ground pressure
- 16,500 -lb hydraulic winch
- One-piece rubber track for easy maintenance

