

XT66



Specifications-Technical Data

- | | | | |
|----------------------------------|--|------------------------------|---|
| Engine..... | Kubota 1505T 44 HP Turbo Diesel | Fuel Capacity..... | 10.5 Gal (US) Aprox. 12 Hrs Run Time |
| Drive System..... | Direct Drive, Closed Loop Hydrostatic | Towing Capacity..... | 5,000 Lbs |
| Water Propulsion..... | Hydraulically Driven Dual 11" Bronze Props | Ground Pressure..... | 1.4 PSI (16" Track)/1.1 PSI (20" Track) |
| Tri-Mode Drive..... | Wheels Only, Props Only or Props & Wheels | Hyd. Tank Capacity | 11 Gal (US); SCH 525 Synthetic |
| Electrical System..... | 12 Volt with 60 Amp Alternator | Unit Dry Weight..... | 3,300 Lbs |
| Battery..... | Ultima Gell Cell | Payload Capacity..... | Land 1,600 Lbs; Water 1,200 Lbs |
| Park/Emergency Brake... | Shot Pin to Disc Positive Lock | Seating | 6 Adults |
| Instrumentation..... | Marine Grade Components | Land Speed..... | 15 MPH |
| Body Construction..... | 3/16" and 1/8" Full-Weld Aluminum. | Speed in Water | 4-5 MPH |
| Bilge Pump..... | 1250 GPH 12 Volt with Auto/Man. Switch | Ground Clearance... | 16" (Center) |
| Hydraulic Oil Cooler..... | Thermo-Controlled Forced Air | Tracks. | 16" or 20" Industrial Rubber |

